

Coslight Polymer Li-ion Battery

Model	Nominal Capacity (mAh) Discharge current:0.2C	Voltage (V)	Dimension (mm)		
			Thickness Tolerance(+0/-0.5)	Width Tolerance(+0/-1.0)	Height Tolerance(+0/-1.0)
CA581730	250	3.7	5.8	17.5	30.5
CA801730	350	3.7	8	17.4	30.2
CA461946	400	3.7	4.6	19	46
CA402025	150	3.7	3.9	20.4	25
CA482030	250	3.7	5	20.5	30
CA702030	350	3.7	8.7	20.5	30.5
CA502430	300	3.7	5	24	30
CA303139	300	3.7	3.1	29.8	37
CA623046	970	3.7	6.2	30	46
CA403064	750	3.7	3.85	30	62.5
CA103048	1500	3.7	10.0	30.4	48.5
CA053048	700	3.7	5.0	30.5	48.5
CA4832D8	2000	3.7	4.8	32.5	138.5
CA433381	1430	3.7	4.35	33.5	81.5
CA443280	1500	3.7	4.5	32	80
CA433382	1450	3.7	4.4	33	82.5
CA323450	530	3.7	3.25	34	50
CA383450	650	3.7	3.8	34	50
CA853465	1950	3.7	8.5	34	65
CA453450	800	3.7	4.5	34.5	50.5
CA553450	1060	3.7	5.9	34.5	50.5
CA383456	700	3.7	3.8	34.5	56.5
CA503456	1000	3.7	5	34.5	56.5
CA6535A4	2750	3.7	6.55	35.2	105
CA523635	620	3.7	5.25	35.3	35
CA473671	1620	3.7	4.8	36.5	71.5
CA483671	1720	3.75	4.8	35.5	70.5
CA603696	2150	3.7	5.7	35.9	96.5
CA883681	2900	3.7	8.8	36	81
CA553759	1400	3.7	5.5	37	59.2
CA353762	1080	3.7	3.85	37	62
CA503759	1330	3.7	5	37.5	59.5
CA603759	1500	3.7	6.4	37.5	59.5
CA633764	1750	3.7	6.3	37.5	64
CA753783	2700	3.7	7.5	37.5	83
CA053946	1030	3.7	5.1	38.4	46.5
CA043946	930	3.7	4.3	38.48	46.5
CA393849	750	3.7	3.9	38.6	47.7
CA503965	1500	3.7	5	38.6	65
CA663974	2500	3.7	6.6	39	74
CA574060	1900	3.7	5.9	40.5	60.5
CA8040B0	3800	3.7	7.6	40	110.5
CA454061	1280	3.7	4.65	40.5	61

Coslight Polymer Li-ion Battery

Model	Nominal Capacity (mAh) Discharge current:0.2C	Voltage (V)	Dimension (mm)		
			Thickness Tolerance(+0/-0.5)	Width Tolerance(+0/-1.0)	Height Tolerance(+0/-1.0)
CA414161	1280	3.7	4.15	41	60.5
CA464161	1450	3.7	4.75	41	61
CA454161	1560	3.7	4.75	41	61.5
CA3941B0	2200	3.7	4.1	41	110
CA374170	1300	3.7	3.8	41.5	68.5
CA604071	2000	3.7	6.1	41.5	73
CA544180	2000	3.7	5.1	41.5	80.6
CA254160	600	3.7	2.65	41.5	60
CA6541120	3000	3.7	6.5	41.5	120.5
CA4841120	2600	3.7	4.8	41.6	121.2
CA4741C2	2650	3.7	4.8	41.5	122.5
CA894237	1530	3.7	8.9	42.5	37.5
CA454261	1500	3.7	4.6	42	61.5
CA494250	1400	3.7	5	42.5	50.5
CA444273	1500	3.7	4.4	42.5	73.5
CA664364	1900	3.7	6.6	43	64
CA604355	1500	3.7	6.0	43.5	55.5
CA484371	2000	3.7	5	43.5	71.5
CA384471	1700	3.7	4	44.5	71.5
CA854475	3000	3.7	8.6	43.5	75
CA404380	1500	3.7	4	43.5	80.5
CA544380	2200	3.7	5.4	43.5	81
CA7043C4	4000	3.7	7	43.5	125
CA644455	2000	3.7	6.4	44	55
CA374478	1530	3.7	3.7	44	78
CA484486	1900	3.7	4.7	44	86
CA354556	900	3.7	3.5	45	58
CA3345A7	1980	3.7	3.38	45.5	107.5
CA624640	1300	3.7	6	45.4	41
CA484650	1500	3.7	4.9	46.5	50.5
CA7446102	3900	3.7	6.95	46.2	102.9
CA524680	2000	3.7	5.2	46.5	80.5
CA604680	2400	3.7	6	46.5	80.5
CA454780	2000	3.7	4.5	46.6	79.5
CA534768	2150	3.7	5.3	47	70.5
CA644845	1450	3.7	6.2	47.4	44
CA534848	1710	3.7	5.3	48.3	47.6
CA304850	750	3.7	3	48.5	50.5
CA424854	1300	3.7	4.25	47.4	54
CA424854-1	1500	3.7	4.45	47.4	54
CA424854-2	1700	3.7	4.7	48	53.5
CA354860	1300	3.7	3.85	47.4	60.5
CA554742	1450	3.7	5.65	47.5	42.5

Coslight Polymer Li-ion Battery

Model	Nominal Capacity (mAh) Discharge current:0.2C	Voltage (V)	Dimension (mm)		
			Thickness Tolerance(+0/-0.5)	Width Tolerance(+0/-1.0)	Height Tolerance(+0/-1.0)
CA474868	2000	3.7	4.7	48	68
CA694871	3000	3.7	6.9	48.5	71.5
CA504768	2000	3.7	5	47.5	68.5
CA654774	3000	3.7	6.55	47.5	74
CA564889	2700	3.7	5.5	47.5	88.5
CA3148A3	1600	3.7	3.2	47.6	102.5
CA404860	1600	3.7	4.2	48.5	60.5
CA454860	1800	3.7	4.7	48.5	60.5
CA354862	1080	3.7	3.5	48.3	61.5
CA364897	2100	3.7	3.6	48.3	97
CA624932	1000	3.7	6.4	48.4	32.5
CA534961	2030	3.7	5.3	49	61
CA484977	1950	3.7	4.8	49	77.4
CA484980	1950	3.7	4.7	49	80
CA454870	1700	3.7	4.5	49.5	69.5
CA594979	3000	3.7	5.9	49.5	79.5
CA4550F2	4000	3.7	4.6	50	152
CA395170	1650	3.7	3.95	50.5	70
CA555070	2270	3.7	5.5	50.5	70.5
CA325080	1500	3.7	3.2	50.5	80.5
CA385085-1	1600	3.7	3.8	50.5	85.5
CA385085	1800	3.7	3.8	50.5	85.5
CA455085	2200	3.7	4.5	50.5	85.5
CA505098	2850	3.7	5	50.5	98.5
CA655186	3000	3.7	6.5	51	83.5
CA4550100	2500	3.7	4.4	51	100
CA705155	2500	3.7	7	51.5	55.5
CA875186	4000	3.7	8.7	51.2	86
CA605265	2200	3.7	6	52.5	65.5
CA555335	1150	3.7	5.7	52.5	34.5
CA625289	3300	3.7	6.2	52.5	89
CA595356	2430	3.7	6.1	53.5	56.5
CA485383	2100	3.7	4.6	52.75	82.65
CA525385	2840	3.7	5.2	53.5	85.5
CA685255	2000	3.7	6.8	53	54.2
CA655356	2500	3.7	6.5	53.5	56.5
CA485360	2030	3.7	4.9	53.0	60.5
CA295357	800	3.7	2.9	53.5	57
CA545452	2030	3.7	5.5	54.5	52.5
CA425462	1800	3.7	4.25	54.2	62.4
CA595462	2650	3.7	5.9	54.2	62.4
CA475456	1900	3.7	4.85	54.4	56.5
CA435458	1900	3.7	4.6	54	58

Coslight Polymer Li-ion Battery

Model	Nominal Capacity (mAh) Discharge current:0.2C	Voltage (V)	Dimension (mm)		
			Thickness Tolerance(+0/-0.5)	Width Tolerance(+0/-1.0)	Height Tolerance(+0/-1.0)
CA355574	1650	3.7	3.5	54.5	74
CA605585	3700	3.7	6	55.5	85.5
CA3555A3	2200	3.7	3.5	55.5	103.5
CA3555A9	2350	3.7	3.5	55.5	109.5
CA3555B0	2400	3.7	3.55	55.5	110.5
CA505656	2030	3.7	5	56.5	56.5
CA655663	3000	3.7	6.5	56.5	63.5
CA4556C0	3700	3.7	4.5	56.5	120.5
CA505766	2100	3.7	5.35	57	65
CA605794	3400	3.7	6	57.5	94.5
CA395856	1700	3.7	3.95	57.5	56
CA4258B1	3350	3.7	4.2	58.5	111.5
CA3558120	2800	3.7	3.7	58	121.5
CA4458C3	3465	3.7	4.35	58	123
CA5159B5	3800	3.7	4.8	58.7	117.2
CA806073	3800	3.7	7.6	60	73.5
CA4460A6	3000	3.7	4.4	60.5	108
CA6460B0	5000	3.7	6.3	61	109.5
CA4360C4	4300	3.7	4.3	60.5	134.5
CA366170	1680	3.7	3.6	61.5	68
CA456248	1480	3.7	4.3	62.3	48.5
CA396370	2280	3.7	4	63.5	70.5
CA476394	2800	3.7	4.7	63.5	94.5
CA746469	3700	3.7	7.4	64	69
CA466548	1550	3.7	4.6	65.5	48.5
CA2865B4	2130	3.7	2.8	65.5	114.5
CA336594	2080	3.7	3.3	65.5	94.5
CA336686	2200	3.7	3.3	66	86.5
CA506686	3000	3.7	4.7	66	86.5
CA576688	3700	3.7	5.65	66.2	87.8
CA486789	3700	3.7	4.8	67.5	89.5
CA3467A3	2350	3.7	3.4	67.5	103
CA5067A0	4000	3.7	5	68	100.5
CA556850	1800	3.7	5.2	68.1	50.5
CA326880	2140	3.7	3.2	68.5	80.5
CA4568D0	4250	3.7	4	68.5	130.5
CA456868	2310	3.7	4.5	68.5	68.5
CA4969A4	4320	3.7	4.9	69	104
CA577070	3200	3.7	5.65	70.3	70.5
CA3970C5	4000	3.7	3.9	70.5	125.5
CA357159	1650	3.7	3.5	70.5	59
CA2570D6	2550	3.7	2.5	70.5	136
CA387166	2100	3.7	4.1	71.5	65.5

Coslight Polymer Li-ion Battery

Model	Nominal Capacity (mAh) Discharge current:0.2C	Voltage (V)	Dimension (mm)		
			Thickness Tolerance(+0/-0.5)	Width Tolerance(+0/-1.0)	Height Tolerance(+0/-1.0)
CA4270107-1	3500	3.7	4.2	71.5	108.5
CA297290	2200	3.7	3	72	90.5
CA4572A0	3700	3.7	4.55	72.5	100.5
CA287554	1150	3.7	2.8	75	55
CA3675A3	3200	3.7	3.6	75.5	103
CA447670-1	2500	3.7	4.6	76.5	70.5
CA3076C0	3280	3.7	3	76.5	120.5
CA387681	2600	3.7	3.9	76.5	81.5
CA447670	2500	3.7	4.4	76.8	69.5
CA397647	1530	3.7	3.9	76.9	48.5
CA3378C4	3600	3.7	3.3	78	124
CA448087	3500	3.7	4.4	80	87
CA289791	2860	3.7	2.9	97	91
CA435661	2060	3.75	4.36	56.4	61.5
CA653495	2400	3.7	6.5	34	95
CA866168	4300	3.7	8.5	61	68
CA455368	1910	3.7	4.5	53.5	68.5
CA3282F0	4950	3.7	3.24	82.5	150
CA855669	4060	3.7	8.53	56.7	69.2
CA767282	5300	3.7	7.6	72	81
CA415656	1710	3.7	4.1	55.85	56
CA335381	1700	3.7	3.3	52.5	81
CA425768	2100	3.7	4.25	57	68
CA435186-1	2500	3.7	4.25	51	86
CA504768-1	1910	3.7	5	47.5	68.5
CA605656	2630	3.75	6	56.3	56.5
CA3970C5-1	4010	3.7	3.9	70	125
CA2981B2	3160	3.7	2.9	80.5	112.5
CA684956	2430	3.7	6.7	48.6	55.5
CA505353	1910	3.7	5	53.5	53
CA585372	2950	3.7	5.7	53	72.5
CA675568	3520	3.7	6.7	54.8	68.2
CA515681	3000	3.7	5.1	56	81.2
CA3958116	2730	3.7	3.8	58.5	115.5
CA425284	2530	3.7	4.1	52	84.2
CA455040	1200	3.7	4.6	50.3	40.5
CA387166	2100	3.7	4.2	71.7	66.5
CA545669	2950	3.7	54	53.8	69
CA406175	2365	3.7	4	61.3	74.2
CA545452HV	2180	3.8	5.45	54.5	52.5
CA823456	1800	3.7	8.2	34	56.5
CA4832D8	2000	3.7	4.8	32.8	137
CA625289	3300	3.7	6.2	52.5	89

Coslight Polymer Li-ion Battery

Model	Nominal Capacity (mAh) Discharge current:0.2C	Voltage (V)	Dimension (mm)		
			Thickness Tolerance(+0/-0.5)	Width Tolerance(+0/-1.0)	Height Tolerance(+0/-1.0)
CA7042C1	3500	3.7	7	42	121
CA404862	1650	3.7	4.05	48.5	62.5
CA3555A2	2100	3.7	3.5	54.8	102
CA3314A0	360	3.7	3.3	13.7	100
CA491539P	230	3.7	4.6	15.2	37
CA505858HV	2380	3.8	5	58.3	58.5
CA435067	2000	3.7	4.3	50.5	67.2
CA406175HV	2580	3.8	4.1	61.3	75.2
CA365770	1800	3.7	3.6	56.6	70
CA485360HV	2210	3.8	4.9	53	61
CA3594A4	4400	3.7	3.5	94	104
CA656480	4350	3.7	6.5	64.8	79.5
CA486789HV	3930	3.8	4.8	67.5	89
CA2970B7V	3100	3.75	2.95	70	117
CA3747A7V	2500	3.75	3.7	47	107.5
CA2847A7V	1800	3.75	2.85	47	107.5
CA384876	1800	3.7	3.8	47.5	76.2
CA585870HV	3300	3.8	5.85	58	70
CA3380A7	3530	3.7	3.3	80.7	107.8
CA556859	2720	3.7	5.55	68	59.3
CA563576HV	2150	3.8	5.55	34.9	76.96
CA426080HV	2590	3.7	4.2	60	80
CA425564	2000	3.7	4.2	55.5	64.5
CA366269HV	2000	3.8	3.6	61.5	69.8
CA506070HV	3330	3.7	5.35	60.3	72.5