













전자접촉기 신-구 비교표

		형 명	GMC-9		GMC-12		GMC-18		GMC-22		GMC-32		GMC-40		GMC-50		GMC-65		GMC-75		GMC-85	
생 산 제 품	GMC - 시리즈	정격용량 AC3	200~220V	2.2kW 11A	2.7kW 13A	3.7kW 18A	4kW 20A	5.5kW 26A	7.5kW 35A		11kW 50A	15kW 65A	18.5kW75A	19kW 80A								
			380~440V	2.7kW 7A	4kW 9A	5.5kW 13A	7.5kW 20A	11kW 25A	15kW 32A		22kW 48A	30kW 65A	37kW 75A	37kW 80A								
			500~550V	2.7kW 6A	5.5kW 9A	5.5kW 13A	7.5kW 17A	11kW 20A	15kW 26A		22kW 38A	37kW 60A	37kW 64A	45kW 75A								
		보조접점 (표준)		1a1b	1a1b	1a1b	1a1b	2a2b	2a2b		2a2b	2a2b	2a2b	2a2b								
		부착치수																				
		외형치수 (W×H×D)		44×80×86.8								68×82×94.6		94×122×115.7								
중량 (kg)		0.33			0.37			0.45		1												
단 종 제 품	SMC - 시리즈	정격용량 AC3	200~220V	2.7kW 13A		4kW 20A		5.5kW 26A	7.5kW 35A	11kW 48A	11kW 50A	15kW 65A	19kW 80A									
			380~440V	4kW 9A		7.5kW 20A		11kW 25A	15kW 32A	15kW 35A	22kW 48A	30kW 65A	37kW 80A									
			500~550V	5.5kW 9A		7.5kW 17A		11kW 20A	15kW 26A	15kW 28A	22kW 38A	37kW 60A	45kW 75A									
		보조접점 (표준)		1a	1a1b	2a2b		2a2b	2a2b	2a2b	2a2b	2a2b	2a2b									
		부착치수																				
		외형치수 (W×H×D)		44×77.5×80(10P), 54×77.5×80(15P)		68×90×96		78×90×102		94×120×115.5												
		중량 (kg)		0.28	0.34	0.53		0.61		1.15		1.15										
		GMC시리즈와 취부호환성		○	○	△		△		△		△										
		형 명		CH-3	CH-3N	CH-5		CH-5N	CH-6N	CH-7.5N	CH-10N		CH-15N	CH-20NS								
		CH - 시리즈	정격용량 AC3	200~220V	2.7kW 13A		4kW 20A		5.5kW 26A	7.5kW 35A	11kW 50A		15kW 65A	18.5kW 80A								
380~440V	4kW 9A			7.5kW 20A		11kW 25A	15kW 32A	22kW 48A		30kW 65A	37kW 80A											
500~550V	5.5kW 9A			7.5kW 17A		11kW 20A	15kW 26A	22kW 38A		37kW 60A	45kW 75A											
보조접점 (표준)			1a	1a1b	1a1b		2a2b	2a2b	2a2b	2a2b		2a2b	2a2b									
부착치수																						
외형치수 (W×H×D)			44×78×80(3), 53×78×80(3N)		64×78×81.5(5), 64×78×109(5N)		74×87×103		88×110×118		88×125×137.5											
중량 (kg)			0.33	0.35	0.39		0.44	0.68		1.3		1.5										
GMC시리즈와 취부호환성		○	○	△		△	△		△		△											
















주) 취부호환성 표기

○: 호환가능













△: Option품인 브래킷사용으로 호환 가능(91page 참조)

Contactors & Thermal overload relays

전자접촉기 신-구 비교표

형 명		GMC-100	GMC-125	GMC-150	GMC-180	GMC-220	GMC-300	GMC-400	GMC-600	GMC-800	
GMC - 시리즈	정격용량 AC3	200~220V	25kW 100A	30kW 125A	37kW 150A	45kW 180A	55kW 220A	75kW 300A	110kW 400A	160kW 630A	200kW 800A
		380~440V	50kW 100A	60kW 120A	75kW 150A	90kW 180A	110kW 220A	150kW 300A	220kW 400A	300kW 630A	400kW 800A
		500~550V	55kW 80A	60kW 90A	90kW 140A	110kW 180A	132kW 200A	160kW 250A	200kW 350A	300kW 500A	400kW 720A
	보조접점 (표준)		2a2b	2a2b	2a2b	2a2b	2a2b	2a2b	2a2b	2a2b	2a2b
	부착치수										
	외형치수 (W×H×D)		100×157.4×146.5		120×166×157		138×203×181		163×243×198		285×290×242
	중량 (kg)		2.9	2.9	3.4	5.4	5.4	9.2	9.2	22	22
형 명		SMC-100P	SMC-125P	SMC-150P	SMC-180P	SMC-220P	SMC-300P	SMC-400P	SMC-600P	SMC-800P	
SMC - 시리즈	정격용량 AC3	200~220V	25kW 100A	30kW 125A	37kW 150A	45kW 180A	55kW 220A	75kW 300A	110kW 400A	160kW 630A	200kW 800A
		380~440V	50kW 100A	60kW 120A	75kW 150A	90kW 180A	110kW 220A	150kW 300A	220kW 400A	300kW 630A	400kW 800A
		500~550V	55kW 80A	60kW 90A	90kW 140A	110kW 180A	132kW 200A	160kW 250A	200kW 350A	300kW 500A	400kW 720A
	보조접점 (표준)		2a2b	2a2b	2a2b	2a2b	2a2b	2a2b	2a2b	2a2b	2a2b
	부착치수										
	외형치수(W×H×D)		100×150×136		120×160×145		138×204×174		163×243×195		290×310×234
	중량 (kg)		2.7	2.7	3.3	5.5	5.5	9.5	9.5	24	24
GMC시리즈와 취부호환성		○	○	○	○	○	○	○	○	○	
형 명		CH-25NS	CH-30NS	CH-40NS	CH-50NS	CH-75NS	CH-90NS	CH-100NS	CH-150NS	CH-200NS	
CH - 시리즈	정격용량 AC3	200~220V	22kW 93A	30kW 125A	37kW 150A	45kW 180A	55kW 250A	75kW 300A	110kW 400A	150kW 600A	200kW 800A
		380~440V	45kW 90A	55kW 110A	75kW 150A	90kW 180A	110kW 220A	132kW 265A	200kW 400A	300kW 600A	400kW 800A
		500~550V	55kW 90A	55kW 90A	75kW 120A	110kW 180A	132kW 200A	160kW 230A	225kW 360A	375kW 600A	400kW 720A
	보조접점 (표준)		2a2b	2a2b	2a2b	2a2b	2a2b	2a2b	2a2b	2a2b	2a2b
	부착치수										
	외형치수 (W×H×D)		100×148×151		120×167×168		138×210×194		148×230×209		163×240×231
	중량 (kg)		2.5	2.5	3.4	5.2	5.2	6.7	9	32	32
GMC시리즈와 취부호환성		○	○	○	○	○	○	○	○	○	

전자개폐기 신-구 비교표

		형 명		GMS-9		GMS-12		GMS-18		GMS-22		GMS-32		GMS-40		GMS-50		GMS-65		GMS-75		GMS-85			
생 산 제 품	GMC – 시리즈	정격용량 AC3	200~220V	2.2kW 11A	2.7kW 13A	3.7kW 18A	4kW 20A	5.5kW 26A	7.5kW 35A			11kW 50A	15kW 65A	18.5kW 75A	19kW 80A										
			380~440V	2.7kW 7A	4kW 9A	5.5kW 13A	7.5kW 20A	11kW 25A	15kW 32A			22kW 48A	30kW 65A	37kW 75A	37kW 80A										
			500~550V	2.7kW 6A	5.5kW 9A	5.5kW 13A	7.5kW 17A	11kW 20A	15kW 26A			22kW 38A	37kW 60A	37kW 64A	45kW 75A										
		보조접점 (표준)		1a1b	1a1b	1a1b	1a1b	2a2b	2a2b		2a2b	2a2b	2a2b	2a2b											
		부착치수																							
		외형치수 (W×H×D)		44×128.9×86.8										68×136.5×94.6		94×181.5×115.7									
중량 (kg)		0.46				0.5		0.45		1.12															
단 종 제 품	형 명				SMO-10P		SMO-15P				SMO-20P		SMO-25P		SMO-35P		SMO-48P		SMO-50P		SMO-65P		SMO-80P		
	SMC – 시리즈	정격용량 AC3	200~220V		2.7kW 13A						4kW 20A		5.5kW 26A		7.5kW 35A		11kW 48A		11kW 50A		15kW 65A		19kW 80A		
			380~440V		4kW 9A						7.5kW 20A		11kW 25A		15kW 32A		15kW 35A		22kW 48A		30kW 65A		37kW 80A		
			500~550V		5.5kW 9A						7.5kW 17A		11kW 20A		15kW 26A		15kW 28A		22kW 38A		37kW 60A		45kW 75A		
	보조접점 (표준)			1a	1a1b			2a2b		2a2b		2a2b		2a2b		2a2b		2a2b		2a2b		2a2b			
	부착치수																								
	외형치수 (W×H×D)			44×114×80(10P), 54×114×80(15P)				60×130×96		78×136×102(25P,35P) 78×148×102(48P)		94×173.5×115.5(50P) 94×193×115.5(65P, 85P)													
	중량 (kg)			0.37	0.4		0.64		0.8		0.92		1.51						1.53						
	GMC시리즈와 취부호환성			○	○		△		△		△		△						△						
	형 명				MH-3		MH-3N				MH-5		MH-5N		MH-6N		MH-7.5N				MH-10N		MH-15N		MH-20NS
CH – 시리즈	정격용량 AC3	200~220V		2.7kW 13A						4kW 20A		5.5kW 26A		7.5kW 35A				11kW 50A		15kW 65A				18.5kW 80A	
		380~440V		4kW 9A						7.5kW 20A		11kW 25A		15kW 32A				22kW 48A		30kW 65A				37kW 80A	
		500~550V		5.5kW 9A						7.5kW 17A		11kW 20A		15kW 26A				22kW 38A		37kW 60A				45kW 75A	
	보조접점 (표준)			1a	1a1b			1a1b	2a2b	2a2b	2a2b			2a2b	2a2b			2a2b	2a2b			2a2b			
	부착치수																								
	외형치수 (W×H×D)			44×119×80(3), 53×119×80(3N)				64×121×81.5(5), 64×121×109(5N)		78×141×103		88×200×118		88×125×137.5											
중량 (kg)			0.44	0.46		0.51	0.56	0.90		2		2.5													
GMC시리즈와 취부호환성			○	○		△	△	△		△		△													

















주) 취부호환성 표기

○: 호환가능

△: Option품인 브래킷사용으로 호환 가능(91page 참조)

Contactors & Thermal overload relays

전자개폐기 신-구 비교표

		형 명	GMS-100	GMS-125	GMS-150	GMS-180	GMS-220	GMS-300	GMS-400	GMS-600	GMS-800	
생 산 제 품	GMC – 시리즈	정격용량	200~220V	25kW 100A	30kW 125A	37kW 150A	45kW 180A	55kW 220A	75kW 300A	110kW 400A	160kW 630A	200kW 800A
		AC3	380~440V	50kW 100A	60kW 120A	75kW 150A	90kW 180A	110kW 220A	150kW 300A	220kW 400A	300kW 630A	400kW 800A
			500~550V	55kW 80A	60kW 90A	90kW 140A	110kW 180A	132kW 200A	160kW 250A	200kW 350A	300kW 500A	400kW 720A
	보조접점 (표준)		2a2b	2a2b	2a2b	2a2b	2a2b	2a2b	2a2b	2a2b	2a2b	
	부착치수											
	외형치수 (W×H×D)		114×231.4×146.5		124×260.4×157	138×306.54×181		163×380×198		360×530×262		
	중량 (kg)		3.4	3.4	4	7.9	7.9	11.8	11.8	28	28	
단 종 제 품	형 명		SMO-100P	SMO-125P	SMO150P	SMO-180P	SMO-220P	SMO-300P	SMO-400P	SMO-600P	SMO-800P	
	SMC – 시리즈	정격용량	200~220V	25kW 100A	30kW 125A	37kW 150A	45kW 180A	55kW 220A	75kW 300A	110kW 400A	160kW 630A	200kW 800A
		AC3	380~440V	50kW 100A	60kW 120A	75kW 150A	90kW 180A	110kW 220A	150kW 300A	220kW 400A	300kW 630A	400kW 800A
			500~550V	55kW 80A	60kW 90A	90kW 140A	110kW 180A	132kW 200A	160kW 250A	200kW 350A	300kW 500A	400kW 720A
	보조접점 (표준)		2a2b	2a2b	2a2b	2a2b	2a2b	2a2b	2a2b	2a2b	2a2b	
	부착치수											
	외형치수 (W×H×D)		112×219×136		120.5×250×145	138×282×174		163×358×195		360×530×234		
	중량 (kg)		3.7	3.7	4.8	8.5	8.5	13	13	36	36	
	GMC시리즈와 취부호환성		○	○	○	○	○	○	○	○	○	
	형 명		MH-25NS	MH-30NS	MH-40NS	MH-50NS	MH-75NS	MH-90NS	MH-100NS	MH-150NS		
CH – 시리즈	정격용량	200~220V	22kW 93A	30kW 125A	37kW 150A	45kW 180A	55kW 250A	75kW 300A	110kW 400A	150kW 600A		
		380~440V	45kW 90A	55kW 110A	75kW 150A	90kW 180A	110kW 220A	132kW 265A	200kW 400A	300kW 600A		
		500~550V	55kW 90A	55kW 90A	75kW 120A	110kW 180A	132kW 200A	160kW 230A	225kW 360A	375kW 600A		
	보조접점 (표준)		2a2b	2a2b	2a2b	2a2b	2a2b	2a2b	2a2b	2a2b		
	부착치수											
	외형치수 (W×H×D)		119×250×151		120×275×168	138×317×187(50NS) 148×320×187(75NS)		173×370×201	173×370×223	290×463×327		
	중량 (kg)		3.6	3.6	5	6.6	10	11.5	13.5	37		
GMC시리즈와 취부호환성		○	○	○	○	○	○	○	○			